

PORTABLE AIR CONDITIONERS



PAC-13

PAC-21 & 29

PAC-37

UPC# 686334	Model	BTU	Volts	Weight (LBS)	CFM		Effective Sq. (FT)	Cord Length (FT)	NEMA Plug
					High	Low			
683814	PAC-13	13,200	120	132	357	285	450	6'	5-15P 12AWG
683821	PAC-21	19,500/21,000	208/240	198	464	393	700	6'	6-15P
683838	PAC-29	28,000/29,000	208/240	209	571	500	1100	6'	6-20P
683845	PAC-37	36,000/37,000	208/240	254	882	776	1250	10'	6-30P
683852	PAC-60*	60,000	208/240	661	2000	1870	2000	10'	6-50P

*Image for PAC-60 not shown.

PORTABLE WATER COOLED SPLIT AIR CONDITIONING



PACWS-22

Features

- Compressor time delay
- Compressor overload protection
- Thermostat
- Self-diagnostic
- Defrost cycle
- Condensate pump
- Washable filter
- Off-timer

UPC# 686334	Model	BTU	Volts	Indoor Unit Weight (LBS)	Outdoor Unit Weight (LBS)	CFM		DB Rating	
						High	Low	High	Low
683807	PACWS-22	22,000	240	198	44	671	530	58	54



TPI CORPORATION
~
SUMMER COOLING



Evap-Mini 500

FRONT
Patented



Evap-Mini 700

FRONT
Patented

Evap-Mini - Features

- Lowers temperatures up to 30 °F
- Water level sight tube and sump drain
- 3/4" garden hose connection for longer running
- Durable one-piece, rust free, leak-proof molded Polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability--near maintenance-free operation
- Shipped completely assembled -- ready to operate out of the box

UPC# 686334	Model	Motor HP	Unit AMPS	CFM		Effective Sq. FT.	Internal Water (Gallons)	Dimensions L x W x H (Inches)	Wt (LB)
				High	Low				
539777	EVAP-Mini 500	1/3	2.5	2000	1600	500	10	31" x 29" x 25"	72
539784	EVAP-Mini 700	1/3	5.6	3000	2400	700	16	38" x 29" x 25"	113

16" PORTABLE WORKSTATION EVAPORATIVE COOLER



FRONT

EVAPORATIVE COOLING TEMPERATURE DROPS			
AIR TEMPERATURE	RELATIVE HUMIDITY		
	10%	30%	50%
80°	-22°	-16°	-10°
90°	-25°	-18°	-12°
100°	-29°	-21°	-14°
110°	-32°	-23°	-15°

Patented



BACK

42 Gallon internal water reservoir that allows the unit to operate approximately 8 hours without being connected to an external water source PROVIDES COOLING UP TO A 900 SQ. FT. AREA

Features

- Durable polyethylene housing features leakproof, one piece construction
- Lowers temperatures 15-25 °F depending on climate conditions
- Easy rolling on polyolefin casters (EVAP16-3)
- Shipped completely assembled, ready to use
- Water level sight tube located on front of unit to indicate water level in tank
- Manufactured in USA

Standard Models

UPC#	Model	Motor HP	Unit AMPS	CFM			Effective Sq. FT.	Internal Water (Gallons)	Dimensions L x W x H (Inches)	Weight (LB)
				High	Med	Low				
686334										
874809	EVAP16-3	1/2	4.6	3900	3500	2500	900	42	23 x 37.5 x 59	145

36" & 48" PORTABLE EVAPORATIVE COOLERS



FRONT

**15°F - 25°F OF EVAPORATIVE COOLING
- PLUS -
6°F - 8°F OF WIND CHILL COOLING**



BACK

36" UNIT IS THIN ENOUGH TO FIT THROUGH A STANDARD DOOR.

Features

- 36" and 48" non hazardous location models feature 3/4" garden hose connections for longer operating times.
- Durable polyethylene housing features leakproof, one piece construction
- Lowers temperatures 15-25 °F depending on climate conditions
- Heavy Duty, polyolefin casters on evaporative coolers
- New 3 blade fan blade for quieter operation.
- 120V operation
- Manufactured in USA. Shipped completely assembled, ready to use
- Hazardous location models available

Standard Models

UPC#	Model	Motor HP	Unit AMPS	CFM			Effective Sq. FT.	Internal Water (Gallons)	Dimensions L x W x H (Inches)	Wt (LB)
				High	Med	Low				
686334										
874816	EVAP36-1	1/2	12.4	9600			2500	32	32 x 62 x 67	235
874823	EVAP36-3	1/2	11.5	9600	6600	4800	2500	32	32 x 62 x 67	245
874847	EVAP48-2	1	13.7	22000	----	11000	4000	40	36 x 74 x 86	405

36" & 48" HAZARDOUS LOCATION PORTABLE EVAPORATIVE COOLERS



FRONT



CONTROL
Patented

UPC#	Model	Motor HP	Unit AMPS	CFM			Effective Sq. Ft.	Internal Water (Gallons)	Dimensions L x W x H (Inches)	Shipping Weight (LB)
				High	Med	Low				
686334										
874830	EVAP36-HAZ	1/2	13.4	9600			2500	32	32 x 62 x 67	330
874854	EVAP48-HAZ	1	18	20000			4000	40	36 x 74 x 86	460

- All switches, motors, and cord connections are sealed to prevent sparking in combustible locations.
- Shipped completely assembled, ready to use
- 120/240V operation
- Manufactured in USA